

## BRASS LACQUER THINNER

### PRODUCT CODE:

4T113 Brass Lacquer Thinner

### PHYSICAL PROPERTIES:

Flash Point: 27°C  
Density: 0.924 g/ml  
Appearance: clear, colourless  
Shelf Life: 3 years unopened

### PRODUCT DESCRIPTION AND USES:

Schwartz Brass Lacquer Thinner is a high quality solvent blend used as retarder/reducer for 34C113 Schwartz Acrylic Brass Lacquer to prevent application problems like dry spray and film defects associated with fast drying like orange peel. 4T113 can also be used with Schwartz 1C352 and 1C373 Brass Lacquers.

### PRODUCT ADVANTAGES:

1. High quality and 100% active solvent
2. Excellent clarity
3. Reduces viscosity for lacquer finishes for excellent sprayability
4. Extends dry time to eliminate orange peel effect resulting to smoother finish
5. Helps reduce dry spray

### ENVIRONMENTAL INFORMATION:

VOC: 924 g/L

### APPLICATION DATA:

Suggested Uses: Used for retarder/reducer for Schwartz' 34C113, 1C352, 1C373 and acrylic-based lacquer finishes.

Mixing Ratio: NA  
Pot Life: NA  
Reducer: NA  
Retarder: NA  
Clean-up Solvent: NA

## **DIRECTIONS FOR USE:**

**Surface Preparation:** NA

**Dry Time:** slower than 4T100 Lacquer Thinner

**Ambient Conditions:** NA

**Storage:** Store indoor at room temperature, away from heat, ignition sources, open flames and direct sunlight.

**Application:**

**Warning:** AVOID sparking, use non-sparking tools. Avoid open flames, turn off all pilot lights, ensure that work area is properly ventilated. Soiled rags and waste products may contain combustible liquids or vapours, dispose in accordance with local regulations. Refer to MSDS for information on safe use of this product.

## **LIMITATIONS and WARRANTY**

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job- conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose. Schwartz makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

Schwartz liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which Schwartz product has been applied. Schwartz reserves the right to have the true cause of any difficulty determined by accepted test methods. Schwartz shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF SCHWARTZ, ITS DISTRIBUTORS OR DEALERS.