

## PDQ STRIPPER GELLED

### PRODUCT CODE:

N46C7 PDQ Stripper Gelled

### PHYSICAL PROPERTIES:

Viscosity: 3000 - 4000 cps  
Density: 1.13 g/ml  
Appearance: cloudy liquid  
Shelf Life: 2 years unopened

### PRODUCT DESCRIPTION AND USES:

Schwartz PDQ Stripper Gelled is a fast-acting paint, varnish, enamel and lacquer stripper. It penetrates quickly even on layers of coating and intricate details on furniture. It has an excellent gel structure that does not drip so it clings to the surface making it a very effective paint stripper especially on vertical surfaces.

### PRODUCT ADVANTAGES:

1. Fast acting
2. Aggressively penetrates layers of coating
3. Effectively clings onto any vertical surfaces to ensure better stripping even on hard to reach areas
4. Safe to use in fine furniture and antiques

### ENVIRONMENTAL INFORMATION:

VOC: 685 g/L

### APPLICATION DATA:

Suggested Uses: Used to strip a wide variety of coatings and finishes on wood, metal, glass, fiberglass, plaster, and masonry

Tools: Eye protection, heavy-duty gloves, brush, paint scraper, steel wool, lint-free cloth, drop cloth or newspaper

Mixing Ratio: NA

Pot Life: NA

Reducer: NA

Retarder: NA

Clean-up Solvent: 4T100 Lacquer Thinner

## DIRECTIONS FOR USE:

**Preparation:** Remove any plastic and rubber materials on items to be stripped. Prepare all tools required.

**Dry Time:** NA

**Ambient Conditions and Precautions:** Use in a well-ventilated area. Always wear eye protect and heavy-duty gloves at all times. Do not get in contact with skin.

**Storage:** Store indoor at room temperature, away from heat, ignition sources, open flames and direct sunlight.

**Application:** Protect floor with drop cloth. Apply PDQ Stripper Gelled generously by brush. Allow to penetrate for 10-20 minutes until coating has bubbled and lifted. Remove softened coating by scraping off with a putty knife or scraper and steel wool. For porous substrates like masonry, use a stiff brush instead. Clean area with lint-free cloth dampened with stripper to remove traces of loosened coating or paint. Finally, clean area with lint-free cloth dampened with 4T100 Lacquer Thinner to remove all residues. Wait 24 hours before refinishing.

**Warning:** Do not breathe in fumes. Avoid open flames, turn off all pilot lights, ensure that work area is properly ventilated. Dispose all soiled rags in accordance with local regulations. Refer to MSDS for information on safe use of this product.

## LIMITATIONS and WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job- conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose. Schwartz makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

Schwartz liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which Schwartz product has been applied. Schwartz reserves the right to have the true cause of any difficulty determined by accepted test methods. Schwartz shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF SCHWARTZ, ITS DISTRIBUTORS OR DEALERS.